

Series 900 110°



Technical information

It can be used with doors as thin as 13 mm or with special profiles.

11 mm deep metal cup


110° opening

Possible drilling distance on the door (K): from 3 to 6 mm


Compatible with all traditional Series 200 mounting plates

NOT COMPATIBLE with DOMI® snap-on mounting plates

Space needed to open the door



T=	16	17	18	19	20	21	22	23	24	25	26
K=3 A=	0,5	0,7	0,9	1,2	1,5	1,8	2,4	3,7	5,1	6,5	7,8
K=4 A=	0,5	0,7	0,9	1,2	1,5	1,8	2,1	2,7	4,1	5,5	6,8
K=5 A=	0,5	0,7	0,9	1,2	1,5	1,8	2,1	2,6	3,1	4,1	5,4
K=6 A=	0,5	0,7	0,9	1,2	1,5	1,8	2,1	2,5	3,0	3,5	4,4




T=	16	17	18	19	20	21	22	23	24	25	26
K=3 L=	0,0	0,0	0,0	0,0	0,2	0,5	0,8	1,1	1,4	1,7	1,9
K=4 L=	0,0	0,0	0,3	0,6	0,9	1,2	1,4	1,7	2,0	2,3	2,6
K=5 L=	1,1	1,3	1,6	1,8	2,1	2,3	2,6	2,9	3,1	3,4	3,6
K=6 L=	2,0	2,3	2,5	2,8	3,1	3,3	3,6	3,8	4,1	4,3	4,6

The above values are calculated on the assumption that the doors have square edges. They are reduced if the doors have radiussed edges.

Projection of the door

Projection of the door from the cabinet side at the max. opening. The figures are based on a straight arm hinge, H=0 mm thickness of mounting plate and K value = 3 mm.



"C" value

With this formula you can obtain the max. thickness of the moulded door that can be opened without touching adjacent carcass sides, doors or walls, whilst bearing in mind the above L-K-T values.

