




Häfele Loox LED 2047

Recess mounted light 12 V, 3 W, drill hole diameter: 55 mm

12 V

2

12/24 V



Recess mounting

3000 K	4000 K	5000 K	120°	
560 lx	570 lx	670 lx		250 mm
210 lx	215 lx	245 lx		500 mm
115 lx	115 lx	135 lx		750 mm
75 lx	75 lx	90 lx		1000 mm

- > High-quality metal housing
- > Wide variety of colours and finishes
- > Homogeneous illumination



- > Dimmable: Yes
- > Area of application: For display cabinets, shelving systems and shelves
- > Housing material: Steel
- > Number of LEDs: 24
- > Life time: 30000 h
- > Weighted energy consumption: 3.3 kWh/1000 h
- > Energy efficiency class: A+
- > Mounting: For mounting in drilled hole and clamp fixing
- > Drill hole diameter: 55 mm

**Note**

Degree of protection with surface mounted housing is IP20

**Supplied with**

1 light with 2 m lead



Colour temperature K	Light colour	Luminous flux lm	Wattage W	Luminous efficiency lm/W	Colour rendering index Ra	Stainless steel coloured	Silver coloured	Chrome plated, polished	Black, matt	White, matt
3000	Warm white	210	3	70	90	833.72.390	833.72.340	833.72.300	833.72.420	833.72.410
4000	Cool white	216	3	72	90	833.72.391	833.72.341	833.72.301	833.72.421	833.72.411
5000	Cool white	240	3	80	83	833.72.392	833.72.342	833.72.302	833.72.422	833.72.412

Packing: 1 piece

Adapter	Packing pieces	Cat. No.
12 V 5 12 V Adapter required for connection to the drivers or distributors of the Loox5 system	1	833.95.823


DGH-M 2021, HDE-en, 10/20; Dimensional data not binding. We reserve the right to alter specifications without notice.



2

12/24 V

→ Surface mounted housing



Undermounted light

> Mounting: Screw fixing




Colour/finish	Cat. No.
Stainless steel coloured	833.72.804
Silver coloured	833.72.803
Polished chrome plated	833.72.802
Black	833.72.801
White	833.72.805

Packing: 1 piece

→ Driver set with Häfele Loox5 12 V 6-way distributor

5 12 V

230 V



**Supplied with**

- 1 driver
- 1 6-way distributor
- 1 mains lead 2 m with flat Euro plug

Distributor version	20 W	40 W
With switching function	833.74.653	833.74.654
Häfele Connect Mesh	833.74.650	833.74.651

Packing: 1 set

DGH-M 2021, HDE-en, 10/20; Dimensional data not binding. We reserve the right to alter specifications without notice.

- Loox switches and sensors ▶ MB 2.267
- Connect Mesh control components ▶ MB 2.284