



Häfele Loox LED 3038

Recess mounted light 24 V, 3 W, drill hole diameter: 55 mm

24 V



- > High-quality metal housing
- > Homogeneous illumination




- > Dimmable: Yes
- > Area of application: For display cabinets, shelving systems and shelves
- > Housing material: Steel
- > Number of LEDs: 24
- > Life time: 30000 h
- > Weighted energy consumption: 3.3 kWh/1000 h
- > Energy efficiency class: A+
- > Mounting: For mounting in drilled hole and clamp fixing
- > Drill hole diameter: 55 mm

Supplied with
1 light with 2 m lead

2

12/24 V



Recess mounting

3000 K	4000 K	5000 K	120°	
580 lx	590 lx	710 lx		250 mm
220 lx	220 lx	265 lx		500 mm
115 lx	115 lx	140 lx		750 mm
75 lx	75 lx	100 lx		1000 mm




Colour temperature K	Light colour	Luminous flux lm	Wattage W	Luminous efficiency lm/W	Colour rendering index Ra	Stainless steel coloured	Silver coloured	Chrome plated, polished
3000	Warm white	215	3	72	90	833.75.150	833.75.120	833.75.140
4000	Cool white	225	3	75	90	833.75.151	833.75.121	833.75.141
5000	Cool white	245	3	82	83	833.75.152	833.75.122	833.75.142

Packing: 1 or 50 pieces

Adapter	Packing pieces	Cat. No.
24 V Adapter required for connection to the drivers or distributors of the Loox5 system	1	833.77.841

DGH-M 2021, HDE-en, 10/20; Dimensional data not binding. We reserve the right to alter specifications without notice.

→ Surface mounted housing



Undermounted light

> Mounting: screw fixing



Colour/finish	Cat. No.
Stainless steel coloured	833.72.804
Silver coloured	833.72.803
Polished chrome plated	833.72.802

Packing: 1 or 45 pieces


2

12/24 V

→ Driver set with Häfele Loox5 24 V 6-way distributor

5 24 V

230 V



Supplied with
 1 driver
 1 6-way distributor
 1 mains lead 2 m with flat Euro plug

Distributor version	20 W	40 W
With switching function	833.77.963	833.77.964
Häfele Connect Mesh	833.77.960	833.77.961

Packing: 1 set